


FOREND E.S.E. INSTALLATION DETAILS



The Details of External Lightning Protection Systems

1- E.S.E. Lightning Conductor Head

Early Streamer Emission Lightning Conductor for large area protection.

2- Lightning Conductor Mast


The E.S.E. Lightning Conductor height may be increased by means of an elevation mast. We recommend, Lightning Conductor Mast should be galvanized steel, is to be min. 3 m in length and 60 mm in diameter, down conductors must be fixed with 1 meter max. distance between the conductor spread along the vertical plane.

3- Down and Grounding Conductors

Number of Down - Conductors

Each E.S.E. Lightning Conductor should be connected to the earth termination system by at least one down conductor. Two or more down-conductors are required when:

- The horizontal projection of the conductor is larger than its vertical projection.
 - External Lightning Protection is installed on any structures higher than 28m.
- The down-conductors should be installed on two different main walls.



(Figure 1) - Number of down-conductors

Down-conductors consist of strips, braided cables, or round sections. Their minimum cross-sectional area of 50 mm² is defined in below table.

| Down-conductors | | |
|--------------------------------------------|----------------------------------------------------------------|---------------------------------------------------------------------------|
| Material | Remarks | Minimum dimensions |
| Bare or tin-plated electrolytic copper (1) | Recommended for its good conductivity and corrosion resistance | Strip: 30x2 mm Round section: 8 mm dia.(2) Braided cable: 30x3,5 mm |
| 18/10-304 stainless steel | Recommended in certain corrosive environments. | Strip : 30x2 mm Round section: 8 mm dia.(2) |
| A 5/L aluminium | To be used on aluminium surfaces (cladding, curtain- walls) | Strip : 30x3 mm Round section : 10 mm dia.(2) |

Notes :

(1) Tin-plated copper is recommended in view of its physical, mechanical and electrical properties (conductivity, malleability, corrosion resistance, etc.)


(2) As the lightning current has an impulse characteristic, the flat conductor is preferred to the round conductor since its outside surface area is larger for a given cross-sectional area.

It must be a fixed mounting surface with conductor fixing internal distance is 1 m. It should be installed in such a way that its path is as direct as possible. It should be as straight as possible along the shortest path without sharp bends or upward sections. As seen figure, It is connected d/L. (Figure 2)

Where; d: safety distance, L: the length of conductor according to shock voltages the average max. value, approximately is not be a jumping danger for $L < 20 d$. The down conductors should not be routed along or across electrical conduits. However, when electrical conduit crossing is unavoidable, the electrical conduit should be placed inside a metal screen which extends 1 m beyond the point of crossing. The screen should be connected to the down conductor.

Routing round parapet walls should be avoided. Provisions should be made to ensure that down conductors paths are as direct as possible.

However, a maximum height increase of 40 cm is permissible for passing over a parapet wall with a slope of 45° or less. (Figure 2)



(Figure 2)

4- Protective Cover

It protects the down-conductors against mechanical damages. You can use U profile or pipe. To prevent the lightning charge down, conductors must be connected to pipe or to U profile.

5- Lightning Strike Counter

When a lightning strike counter is used to match the number of lightning stroke it should be installed on the most direct down conductor above the test clamp and in any case at height of about 2m. above the ground level.

6- Test Clamp

According to down conductor, covered plastic, is provided to measure the earth resistance, in an accessible position on each main earthing conductor between earthing electrode and must be over protective tube.

7- Earth Termination

You should use reliable earth electrodes according to EN 62305-3. They shall be extensible and driven as deep as possible in earth starting from a minimum depth of 50 cm in the earth and located at such distance from one and other that maximum current likely to flow through one as they do not significantly effect the potential of the other's (5 m). Earth Resistance is less than 10 Ohm.

8- Mounting

It must be checked after corrosion between different materials and avoided using different materials as much as possible. The wall's surface must not be destroyed to fixing the carrier pole,conductor clips. It must be provided both canal digs for grounding system and ground on which a building must be rebuilt for grounding system.

9- Project

It must be projected to mounting in truth.

10- Test Report

After the installation is finished, earth resistance must be measured by the authorized personel and than it must be reported and approved by an authorized engineer.

Some examples of our installations



Some examples of our installations



Project: Vodafone Park Beşiktaş J.K. İstanbul, Turkey




Project: Fenerbahçe Ülker Stadium in İstanbul, Turkey



Project: Arsenal Soccer Schools in , Thailand



Project: The Coca Cola Factory in Tarija, Bolivia



Project: The Coca Cola Factory in, Georgia

Some examples of our installations



Project: Telecommunications Towers
Camouflaged, **Chile**



Project: Novosibirsk, Administration
Building, Krasny avenue, 17 in **Russia**




Project: Fishing pier in Rufisque, **Senegal**





Project: Edificio Residencial
Míguez, **Uruguay**

Some examples of our installations



Some examples of our installations



Some examples of our installations



Some examples of our installations



Project: Phuket International Airport,
Phuket Province, **Thailand**



Project: Sochi International Airport,
Sochi, **Russia**



Project: Garages of Metro Line 12 in
Mexico City, **Mexico**



Project: Orange Line Metro Train Station,
Lahore, **Pakistan**

Quality Certificates



Some of Forend Technical Products

FOREND E.S.E. Lightning Conductors

FOREND PETEX-L

FOREND EU-M

FOREND EU



Lightning Strike Counter

To know you had a lightning strike!!!



Produced according to IP 68
Currents detected from 1 kA to 100 kA
Testable with 9 V battery
Resetable for just Digital Counter

Active Lightning Conductors Tester

FOREND active lightning conductors can be checked by a FOREND L.C. tester any time.



Cable Lugs

Best quality and best price for your cables!



6 mm² - 600 mm²;
wide range of products

Conductor Fixing Plastic Clamps

Rustproof, light, easy montage



1x50 mm²

2x50 mm²

30x3 mm



2.0" - 2x50 mm²

Earthing Grids

The same performance but more economic and lighter than same dimension copper plates.

Dimensions
100x50 cm - 2.00 m



Inspection Pits

For easy resistivity control



- Endurance against 65 tonnes
- Easily transportable

TAM (Technical Additive Materials)

More effective material to solve the toughest earthing problems



TAM comes in easy to handle 10 kgs per bag.
TAM lowers resistance to earth.
TAM performs in all soil types.

Led Beacon Lights Maximum Performance



Produced according to IP 65

| | FLB 10 S |
|----------------------------|-----------------------------------------------|
| Operation Voltage | 12 V DC; 24 V DC; 48 V DC; 110 V AC; 220 V AC |
| Power Consumption | 6 W |
| Max. Operating Life | 100 K |
| Luminous Flux (theoric) | >32cd |
| Height x Diameter (mm) | 215x115 |
| Operating Temperature (°C) | -40 °C to + 85 °C |
| Weight (kg) | 1,45 |

Forend Exothermic Welding System

For longer and stronger conductivity
than mechanical connection



Reference Countries

European Union

Bulgaria, Czech Republic, France, Germany, Greece, Ireland, Lithuania, Poland, Portugal, Romania, Slovakia

Eastern European And Eurasian Countries

Azerbaijan, Georgia, Kazakhstan, Russian Federation, Serbia, Ukraine

North America

United States of America

Latin America

Argentina, Bolivia, Chile, Costa Rica, Ecuador, Guatemala, Mexico, Peru, Uruguay

Asia

Bangladesh, Hong Kong, India, Indonesia, Malaysia, Pakistan, Philippines, Singapore, Sri Lanka, Taiwan, Thailand, Vietnam

Middle East

Iran, Iraq, Jordan, Lebanon, Oman, Syria, United Arab Emirates

Africa

Algeria, Angola, Burkina Faso, Cameroon, Djibouti, Egypt, Ethiopia, Ghana, Ivory Coast, Madagascar, Morocco, Nigeria, Rwanda, Senegal, South Africa, Tunisia



Halaskargazi Caddesi No.141 Şişli Sarayı Apt. K.4 D.7

34381 Osmanbey - ŞİŞLİ - İSTANBUL / TURKEY

Ph: +90 212 291 51 63 (2 Lines) Fax: +90 212 291 51 65

www.forend.com.tr • export@forend.com.tr

Authorized Distributor